

Use an API Key to Make Calls

Last Modified on 05/13/2021 12:58 pm MDT

To use an API key in the Swagger interface:

1. Log in as an admin and select the appropriate org, if required.
2. Navigate to Admin > Swagger Docs.
3. Click the resource from the list to open the Swagger interface in a new tab.
4. Expand a supported endpoint.
5. Enter the API key in the **x-api-key** field to authenticate the call.
6. **Optional:** If impersonation is enabled, enter the ID of the user who will be impersonated. Impersonation can only be enabled by a member of Resolver Support. See [Impersonation with an API Key](#) for more details.

The screenshot shows the Swagger UI for the 'file' service. The endpoint `POST /data/file/file` is selected. The response class is 'OK' with a status of 200. The response content type is set to 'application/json'. The parameters section is highlighted with a green box and contains the following table:

Parameter	Value	Description	Parameter Type	Data Type
x-api-key	<input type="text"/>		header	string
impersonate-user-id	<input type="text"/>		header	double
file	<input type="file" value="Choose File"/> No file chosen		formData	file

Below the parameters table is a 'Try it out!' button.

The POST /data/file/file endpoint in the file service.

7. Complete the remainder of the fields as required.

Example

RESOLVER

```
curl -X POST --header 'Content-Type: multipart/form-data' --header 'Accept: application/json' --head
```